D	URGA VALVES PVT LTD	REF. N	0. :		_
	Howrah - 711104 (An ISO-9001 Company)	Contrac	tor:	DVF	
SI. NO.	DESCRIPTION		DETAILS		
1	TAG / SERIAL NO.	-			
2	TYPE OF VALVE	DUAL PLATE CH	DUAL PLATE CHECK VALVE		
3	МАКЕ	'DURGA/DVPL'	'DURGA/DVPL'		
4	STANDARD	As per manufacturer Std, Ref API-594			
5	SIZE				
6	QTY.				
7	PRESSURE RATING	PN- 1.0/PN-1.6	PN- 1.0/PN-1.6/PN-20/PN-2.5		
8	END CONNECTION	Flanged	Flanged		
	MATERIAL OF C	ONSTRUCTION			
9	BODY	DUCTILE IRON	DUCTILE IRON GGG 50		
10	DISC (2 Pcs.)	DUCTILE IRON	DUCTILE IRON GGG 50		
11	BODY SEAT	S.S. to AISI 30	S.S. to AISI 304		
12	DISC SEAL	EPDM	EPDM		
13	HINGE PIN	S.S. to AISI-41	S.S. to AISI-410		
14	STOP PIN	S.S. to AISI-41	S.S. to AISI-410		
15	RETAINER/PLUG	S.S. to AISI-41	S.S. to AISI-410 / 304		
16	LUG BEARING	G.M. / TEFLON	G.M. / TEFLON		
17	SPRING	Spring Steel/ S	Spring Steel/ SS 304		
18	LIFTING HOOK		Carbon Steel (Forged Quality)		
	OTHERS PA	RTICULARS			
19	TESTING STD.	API-598	API-598		
20	MAX. PRESSURE DROP AT DESIGN FLOW RAT	E 0.5 MWC	0.5 MWC		
21	MAX. PRESSURE LEAKAGE RATE	7.0 cc/hr/mm d	7.0 cc/hr/mm diameter.		
22	CLOSURE CHARACTERISTIC		High speed closing & minimum slam condition when closing		
23	OPERATION	Automatically /	Automatically / Self		
24	PAINTING	As per Appvd. I	As per Appvd. Drg.		
25	MARKING		'Brand'/Size/PN-Rating/Arrow Mark/Heat No. & Sr. No.		
	 NOTES : ★ VALVES ARE SUITABLE FOR USE VERTICAL/HORIZONTAL INSTALLATION. ★ DISC FULLY OPEN (85 deg.) UNDER NORMAL FLOW. Scope Of Inspection : a) Dimensional & Visual c) Hydro test pressure for body & seat to be checked by client d) Internal test report of materials (Physical & Chemical) to be reviewed by client 				
		DESIGN	APPD	DATE:	
0	For Approval 05/12/13	PREP	DATA SHEET NO.		
REV. NO	DATE DESCRIPTION	СНКД	DVPL/DUAL PLATE/01		